

TECHNICAL DATA SHEET

TOFIL 803

Alkali and Efflorescence-Resistant Primer and Sealer

PRODUCT DESCRIPTION:

TOFIL 803 is a low-odor, water-based flat primer paint specially formulated for all types of masonry, concrete, bricks, and drywall. It's non-toxic and non-flammable and has good sealing, hiding, and adhesion capability. It is ideal for both interior and exterior surfaces of commercial and residential structures.

CUSTOMER BENEFITS:

- Ready-to-use
- Easy application
- Good adhesion to substrate
- Prevents efflorescence
- Cost and time saving
- Excellent hiding power

INSTRUCTION FOR USE

SURFACE PREPARATION

All surfaces must be clean and dry, free from dust, oil, grease, and other contaminants that may affect the adhesion of the paint to the surface. Dents, seams, and rock pockets exceeding 3 mm must be repaired before the application.

THINNING

Use at package consistency or thin down with water as necessary.

TINTING

It may be tinted with **SINCLAIR ACRI-COLORS** to produce the desired color. For darker shades, factory tinting is required.

APPLICATION

New concrete must be cured for at least 28 days before applying **TOFIL 803**. For **TOFIL 801 SKIMCOAT SF**, wait for 7 days on interior and 3 days for exterior before applying **TOFIL 803**. It may be applied with a brush, roller, or spray.

DRYING TIME

Approximately 1 to 2 hours. Allow 2 hours before applying the second coat.

FOR PLASTER, CONCRETE

Primer : **TOFIL 803**

Topcoat : 2 coats **SINCLAIR SEMI-GLOSS LATEX**
or **SINCLAIR GLOSS LATEX PAINT**

COVERAGE

Recommended coverage:

5.00 – 6.25 m² / liter at 50 microns dry film thickness per coat.

Note: *The coverage rates provided above are for guidance purposes only. Actual usage may vary depending on the specific substrate conditions and application methods.*

PACKAGING

TOFIL 803 is available in 1 liter, 4 liter, and 16 liter pail.

STORAGE AND HANDLING

TOFIL 803 has a minimum shelf life of 36 months if maintained in dry storage conditions in unopened containers.

PRECAUTIONS

HEALTH AND SAFETY

TOFIL 803 is non-flammable.

Refer to the latest Safety Data Sheet (SDS) for comprehensive safety information on the proper handling of this product.

WARRANTY AND DISCLAIMERS

The information provided in this technical data sheet is based on our best knowledge and testing methods. Any product use outside of specifications or improper storage or installation voids any warranty. Users are encouraged to conduct their own testing to assess product suitability. Always consult the product's safety data sheet (SDS) for safety guidelines and follow recommended precautions. We reserve the right to update this data sheet without notice, and users should ensure they have the latest information.